

CHARLOTTE...

Department of General Services – City Procurement

Addendum	#4	

Firefighting Turnout Gear ITB # 269-2020-031

To: All Prospective Bidders

Date: 3/18/2020

Subject: Addendum # 4 – ITB # 269-2020-031 Firefighting Turnout Gear

Please note the specification changes/modifications below for the ITB

Item #	Page #	Section #	Specification	Modifications and Questions
1	10	1.8	How to Submit Bid Responses	 Modification: Change have been made regarding hand delivering bid packages to the Government Center and attending the bid opening. The second paragraph has been modified to read as follows: The Charlotte-Mecklenburg Government Center (CMGC) has been closed to the public. If the bid package cannot be mailed, please contact Shiela Bailey at 704-336-8084 and schedule a time for the bid package to be delivered. Bidder must call when they arrive at the building and the staff person will go outside to receive the bid. The bid package will need to be left on a table and the bidder can watch the staff person pick up the package. Please allow time for this process if delivering in-person to the CMGC.
2	11	1.9	Bid Openings	 Addition: Add the following language to the ITB: Bid Openings will be conducted via WebEx video and teleconference line. To livestream the bid opening via WebEx, email Shiela Bailey at shiela.bailey@charlottenc.gov for an email link to join the Webex Meeting. Instructions to use WebEx are below. Bidders can also dial 704-336-5485 to attend via teleconference. Joining a WebEx Meeting: You can join the meeting by clicking on the "Join WebEx Meeting" link in your email invitation If this is your first-time using WebEx, there is a two-step process to follow: Step 1: Whether the link opens in Google

Item #	Page #	Section #	Specification	Modifications and Questions
				 Chrome or Internet Explorer, you will be asked to install the WebEx application. You can either choose to install it or click "Run a temporary application" if you think you will rarely use WebEx. If you receive an error message about needing administrative rights to install the application, simply choose the "Run a temporary application" option. If you are still having difficulty, WebEx often works better in Google Chrome. Make sure that Java is installed. Step 2: Enter your name and email address You will automatically join the meeting To establish voice communication, click the ellipse ("") under "I Will Call In" Call in using the toll number (650 area code) and enter the access code and Attendee ID when prompted.
3	87	3	Barrier Hoods	Modification: Separating the specifications for the Fire-Dex H-41 Barrier Hood and the PGI Barriaire Gold Hood requirements. The specifications for the PGI Barriaire Gold Hood are provided on revised specification sheets.
4	112	4	Form 5	Modification: Part Number added to Price Sheet for PGI Barriaire Gold Barrier Hood.

In order to constitute a complete bid response you must acknowledge receipt of this addendum with the Addenda Receipt Confirmation Form in Section 4 of the ITB in your Bid. *Any Bidder not acknowledging receipt of an issued addendum may not be considered.*

In the event additional changes or clarifications to this ITB are warranted, all Bidders are responsible for monitoring the City's <u>Contract Opportunities</u> site or <u>www.ips.state.nc.us</u> or for additional addenda.

We appreciate your interest in doing business with the City and look forward to receiving a Bid from your company.

Sincerely,

Lenore Bishop Procurement Officer

cc: ITB Team ITB File

PGI

BARRIAIRE GOLD HOOD

INSERT BIDDER'S PROPOSED ALTERNATE PRODUCT/BRAND/MODEL NUMBER:

3979471-7

REQUIREMENTS:

NFPA COMPLIANCE / REQUIRED	YES	NO	EXCEPTIONS:
CERTIFICATIONS: UL Classified to NFPA 1971 Standard on Protective Ensembles for Structural Fire Fighting and Proximity Fire Fighting – Current			
Edition. Certification to the NFPA 1971, 2018 Edition Option for Particulate Protection. All materials and construction will meet or exceed NFPA Standard			
1971, current edition.			
PARTICULATE (CARCINOGEN) BLOCKING: The hood shall incorporate a particulate blocking media that has a filtration efficiency of at least 90% for each particle size ranging from 0.1 to 1.0 microns. The Nomex® Nano Flex particulate barrier shall provide filtration throughout the entirety of the hood, including top of head, around the elastic face opening, and complete coverage of the bib. Particulate coverage shall extend throughout entire head area and front & back bib.	YES	NO	EXCEPTIONS:
CONSTRUCTION: Hood shall be constructed of a 3- layer quilted composite fabric with a particulate barrier of Nomex® Nano Flex sandwiched between interior and exterior layers of a 5.5-ounce jersey knit fabric with a 55% mechanical stretch. Particulate coverage shall extend throughout entire head area and front & back bib. Panel at crown shall be one continuous piece of quilted composite extending from top of face opening and shall be seamed from top of face opening to the bib seam.	YES	NO	EXCEPTIONS:
Face opening shall be circular and serged with x-heavy duty ¹ / ₂ " wide elastic around the perimeter. Elastic shall be folded under ¹ / ₂ " and cover-stitched. Face opening shall stretch to approximately 15". Bottom hem of hood shall be bound with self-material bias.			
All stitching shall conform to Federal Standard 751 with all major seams flat seam assembled with stitch type 607. Elastic around face opening shall be serged in with stitch type 504 and reinforced with bottom cover-stitch type 406. All binding shall be applied with bottom cover-stitch type 406.			

DESIGN: Hood shall be offered in universal sizing.	YES	NO	EXCEPTIONS:
The panel at the crown shall measure approximately 4"	1 10	110	
in width at top of face opening and extend			
approximately 20" in length from top of face opening			
to top of rear bib seam. The circular face opening shall			
measure approximately 5" in diameter. Measurement			
from top edge of left shoulder cap continuing around			
bottom of bib to top edge of right shoulder cap shall be			
approximately 29". Width from top outer edge of			
each shoulder cap shall measure approximately 20.5".			
Width from top inner edge of each shoulder cap shall			
measure approximately 12.5". Front length of hood			
from top to bottom shall measure approximately 22".			
Back length of hood from top to bottom shall measure			
approximately 22". Width of hood above face			
opening to back shall measure approximately 10.5".			
Width of hood mid-face opening to back shall measure			
approximately 9.25". Width of hood 1" below			
bottom of face opening to back shall measure			
approximately 11.5". Length of hood at mid-crown to			
mid-bib from top to bottom shall measure			
approximately 20.5". Length of hood from center			
upper edge of face opening to bottom center edge of			
bib shall measure approximately 12.5".			
The second			
	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster.	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate.	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate. Particulate barrier used throughout hood shall be	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate.	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate. Particulate barrier used throughout hood shall be Nomex® Nano Flex.	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate. Particulate barrier used throughout hood shall be Nomex® Nano Flex. CRAQ SPUN® AR Teijinconex® thread shall be used	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster.Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate.Particulate barrier used throughout hood shall be Nomex® Nano Flex.CRAQ SPUN® AR Teijinconex® thread shall be used throughout the hood to further enhance the particulate	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate. Particulate barrier used throughout hood shall be Nomex® Nano Flex. CRAQ SPUN® AR Teijinconex® thread shall be used throughout the hood to further enhance the particulate barrier durability.			
 MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate. Particulate barrier used throughout hood shall be Nomex® Nano Flex. CRAQ SPUN® AR Teijinconex® thread shall be used throughout the hood to further enhance the particulate barrier durability. COVERAGE: The hood shall incorporate the 	YES	NO	EXCEPTIONS:
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate. Particulate barrier used throughout hood shall be Nomex® Nano Flex. CRAQ SPUN® AR Teijinconex® thread shall be used throughout the hood to further enhance the particulate barrier durability.			
 MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate. Particulate barrier used throughout hood shall be Nomex® Nano Flex. CRAQ SPUN® AR Teijinconex® thread shall be used throughout the hood to further enhance the particulate barrier durability. COVERAGE: The hood shall incorporate the particulate barrier filtration Nomex NanoFlex throughout the entirety of the hood, including top of 			
MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster.Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate.Particulate barrier used throughout hood shall be Nomex® Nano Flex.CRAQ SPUN® AR Teijinconex® thread shall be used throughout the hood to further enhance the particulate barrier durability.COVERAGE: The hood shall incorporate the particulate barrier filtration Nomex			
 MATERIALS: Exterior layer shall be a 5.5-ounce jersey knit blend of meta-aramid, para-aramid, high tenacity nylon & anti-stat. A DWR (Durable Water Resistant) finish shall be applied to reduce build-up of toxic residue, enhance the release of contaminants during washing, and enable hood to dry 2x-3x faster. Interior layer shall be identical in composition to the exterior layer, but without the DWR application so moisture may be pulled from the wearer's skin and transferred toward the exterior layer to evaporate. Particulate barrier used throughout hood shall be Nomex® Nano Flex. CRAQ SPUN® AR Teijinconex® thread shall be used throughout the hood to further enhance the particulate barrier durability. COVERAGE: The hood shall incorporate the particulate barrier filtration Nomex NanoFlex throughout the entirety of the hood, including top of 			

 LABELING AND USER INFORMATION: Each hood shall be labeled to identify material contents, NFPA acceptance, UL Classification, Date of Manufacture, Lot Tracking Number, Style Number, Statement of Made in USA and care instructions. The UL Certified FR label shall facilitate tracking and identification through barcoding, sequential numbering, and personalization with a permanent identification with a laundry marker. Each hood shall include a complete user information guide. 	YES	NO	EXCEPTIONS:
WORKMANSHIP AND QUALITY CONTROL: All hoods shall be made in a craftsman-like manner and shall be inspected during manufacturing, final trimming, and packing to ensure consistent quality and adherence to this specification.	YES	NO	EXCEPTIONS:

PRICING SHEET

ITB # 269-2020-031

FIREFIGHTING TURNOUT GEAR

The undersigned proposes to furnish the following items in strict conformance to the bid specifications and bid invitation issued by the City of Charlotte for this Bid. Any exceptions are clearly marked in the attached copy of bid specifications. Please do not include taxes in your Bid.

ITEM	DESCRIPTION	BRAND	STYLE	UOM	EST	UNIT	EXTENDED	BIDDER'S	EQUIVALENT	EQUIVALENT
		NAME	NUMBER		ANNUAL QTY	PRICE	PRICE	EQUIVALENT	UNIT PRICE	EXTENDED PRICE
1	Kombat Flex Turnout Coat	Globe	D2257G	EA	250					
2	Athletix Turnout Coat	Globe	A42NG10	EA	250					
3	Nomex Coat	Globe	D0757G	EA	10					
4	GPS Turnout Pants	Globe	F2257G	EA	250					
5	PBI Max 7oz. Turnout Coat	FireDex	FXRCTPBI7EF	EA	250					
6	PBI Max 7oz. Turnout Pants	FireDex	FXRPTPBI7EF	EA	250					
7	Tecgen 71 Turnout Coat	FireDex	FXRCTTG71EF	EA	250					
8	Tecgen 71 Turnout Pants	FireDex	FXRPTTG71EF	EA	250					
9	Tecgen 51 Technical Rescue Coat	FireDex	TECGEN 51	EA	100					

10	Tecgen 51 Technical Rescue Pants	FireDex	TECGEN 51	EA	100				
11	Energy Turnout Coat	Innotex	Energy	EA	250				
12	Energy Turnout Pant	Innotex	Energy	EA	250				
13	Particulate Barrier Hood	FireDex	H-41	EA	1200				
14	Particulate Barrier Hood	PGI	BarriAire Gold 3979471-7	EA	1200				
15	Particulate Blocking Hood	Innotex	Gray 35	EA	1200				
16	Asheville - Turnout Gear Coat	Morning Pride	LTO-4li3TB	EA	50				
17	Asheville - Turnout Gear Pant	Morning Pride	LTO-4li3PB	EA	50				
						TOTAL:		TOTAL:	
		PRICING	OPTIONS:						
18	Guard Jacket Component	Globe							
19	Guard Pant Fly Component	Globe							
20	Guard Pant Cuff Component	Globe							

Total Bid Price must include all equipment, labor, delivery, installation, consultation, vendor profit and all other costs associated with this project. No additional costs will be allowed.

1. Administrative Fees:

The Company **shall** submit a <u>minimum</u> of one (1) percent of overall CCPA Program spend by the City and Participating Public Agencies during the term of the Contract to the City as an Administrative Fee. The Administrative Fee shall be paid no later than thirty (30) days after both parties mutually agree to the quarterly report outlining the CCPA spend. The Company shall indicate their Administrative Fee below:



2. Non-Core Items – Fixed Percentage Discount

The Company **shall** provide a fixed percentage discount from the List Price (list price less discount) included in the Company's most current full line catalog identified in the Specifications for all other items (Non-Core) included in the catalog for the life of the Contract.

a. Insert the verifiable catalog name/edition: _____

b. Insert the fixed percentage discount for Non-Core Items:

3. Pricing Incentives and Rebates:

Please identify any incentive and rebates offered based on volume, dollar amounts, core credits or other criteria below:

Rebate Description	Amount or Percentage

Payment Terms:

Delivery After Receipt of Order: ______The undersigned hereby certifies the Bidder has read the terms of this Bid document, including the sample Contract (Section 5) and is authorized to bind the firm to the information herein set forth.

Date:	Company:
By:	Signature:

Print name and title of signatory